



## TRASK Shelf Bracket

**CALIFORNIA PROPOSITION 65 WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov).

## PARTS INCLUDED

- 2pcs bracket
- 2pcs mounting template
- 4pcs  $\phi$ 4X40mm wall mounting screws
- 4pcs  $\phi$ 12.5X40mm dry wall Anchors
- 2pcs  $\phi$ 4X19mm shelf mounting screws

**Maximum total weight capacity for this product is 50lbs (22.7kgs)**

## MOUNTING INSTRUCTIONS FOR TYPICAL DRYWALL APPLICATIONS

Note: Consult your local hardware store for proper mounting to other wall materials.

Tools Required: Phillips and slotted screwdriver, Pencil.

1. Place one of Shelf Brackets in the desired location, Set the shelf bracket aside.
2. Place mounting template on the wall, Using a pencil, Mark the locations of the upper bracket drywall anchors
3. Using a Phillips head screwdriver, pierce the tip of the anchor into the wall. Do not push or “pound” the anchors into the wall, they are designed to bore into the wall like a screw. Turn clockwise until the anchor is flush with the wall.
4. Insert a screw into upper anchor. Turn the screw clockwise until the screw head is about 0.185inch\* from the wall.
5. Hang the shelf bracket on the protruded screws. Mark the locations of the lower bracket drywall anchors
6. Set the shelf bracket aside , Repeat step 3
7. Hang the upper bracket on the protruded screws, Insert a screw through the bottom screw hole of bracket and Turn the screw clockwise just until you feel resistance.
8. Use a tape measure and level, determine the location for second shelf bracket, repeat step 2&3&4&5&6&7
6. Slide shelf into brackets, secure it with set screws.

## CLEANING INSTRUCTIONS

1. Dust often using a clean, soft, dry and lint-free cloth.
2. Blot spills and wipe with a clean, damp cloth immediately.
3. We do not recommend the use of chemical cleansers, abrasives or furniture polish on our lacquered finish.
4. Hardware may loosen over time. Periodically check to make sure all connections are tight. Re-tighten if necessary

## 8in Bracket

## 10in Bracket

