

REJUVENATION

Mirror Bentwood Round 30in Walnut

PARTS INCLUDED:

Mirror	1 pc
Screws	2pcs
Drywall anchors	2pcs

TOOLS REQUIRED: Phillips screwdriver, pencil, Stud finder.

MOUNTING INSTRUCTIONS FOR TYPICAL DRYWALL APPLICATIONS

Note: Consult your local hardware store for proper mounting to other wall materials.

Please note that a paper template is included with this item to help locate the insertion points of the mounting hardware on the wall.

1. Position the provided template on the wall and make sure it is level (use the two D-rings on the template as a reference). Mark the D-ring positions on the wall by piercing the template with a sharp pencil.
2. Install the anchors at each insertion mark. Using a Phillips head screwdriver, pierce the tip of the anchor into the wall and turning clockwise until anchor is flush with the wall. *Do not “push” or pound the anchors into the wall, they are designed to bore into the wall like a large screw.* Then use the screwdriver to secure a screw into each installed anchor. Rotate the screw clockwise until the screw head is about 3/8” from the wall.

Note: If either insertion mark aligns to an inner wall stud (use a stud finder to determine this), do not use an anchor at that location – use the screw only. Use the screwdriver to secure a screw into the wall directly and leaving the screw head about 3/8” from the wall.

3. With the help of another person, carefully lift the item against the wall and positioning the two D-rings over the protruding screw heads. Lower the item so that the screws support the full weight of the mirror.

CLEANING INSTRUCTIONS

- Wipe with a soft, dry cloth.
- To protect the finish, avoid the use of all chemicals and household cleaners.
- A household glass cleaner may be used to clean the mirror surface, but apply the cleaner to a clean cloth first and then use the cloth to clean the mirror surface. Avoid spraying the cleaner directly onto the mirror frame.

